

## HIGH SPEED SWITCHING APPLICATION

## 1SS374

## ■ Features

- Small package
- Low forward voltage : $V_R = 0.23V$ (Typ). @ $I_F = 5mA$

■ Absolute Maximum Ratings  $T_a = 25^\circ C$ 

Parameter	Symbol	Rating	Unit
Maximum(Peak) Reverse Voltage	$V_{RM}$	15	V
Reverse Voltage	$V_R$	10	V
Maximum(Peak) Forward Current	$I_{FM}$	200*	mA
Average Rectified Current	$I_o$	100*	mA
Surge Current (10 ms)	$I_{FSM}$	1*	A
Power Dissipation	P	150	mW
Junction Temperature	$T_j$	125	$^\circ C$
Storage Temperature Range	$T_{stg}$	-55 to +125	$^\circ C$
Operating Temperature	$T_{opr}$	-40 to +100	$^\circ C$

\* Unit Rating.Total Rating = Unit Rating  $\times$  0.7.

■ Electrical Characteristics  $T_a = 25^\circ C$ 

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Continuous reverse voltage	$V_F$	$I_F = 1 \text{ mA}$		0.18		V
		$I_F = 5 \text{ mA}$		0.23	0.3	
		$I_F = 100 \text{ mA}$		0.35	0.5	
Reverse current	$I_R$	$V_R = 10 \text{ V}$			20	$\mu A$
Total capacitance	$C_T$	$V_R = 0, f = 1.0 \text{ MHz}$		20	40	pF

## ■ Marking

Marking	N9
---------	----