


isc Three Terminal Negative Voltage Regulator

7905


FEATURES

- Output current in excess of 1A
- Output voltage of -5V
- Internal thermal overload protection
- Output transition Safe-Area compensation
- Minimum Lot-to-Lot variations for robust device performance and reliable operation



ABSOLUTE MAXIMUM RATINGS(T_a=25°C)

SYMBOL	PARAMETER	RATING	UNIT
V _i	DC input voltage	-35	V
I _o	Output current	internally limited	
P _{tot}	Power dissipation	internally limited	
T _{OP}	Operating junction temperature	0~125	°C
T _{stg}	Storage temperature	-55~150	°C



DIM	mm	
	MIN	MAX
A	15.50	15.90
B	9.80	10.20
C	4.20	4.50
D	0.70	0.90
F	3.40	3.70
G	4.98	5.18
H	2.68	2.90
J	0.44	0.60
K	12.80	13.40
L	1.20	1.45
Q	2.70	2.90
R	2.30	2.70
S	1.29	1.35
U	6.45	6.65
V	8.66	8.86

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{th j-c}	Thermal Resistance, Junction to Case	5	°C/W
R _{th j-a}	Thermal Resistance, Junction to Ambient	65	°C/W

isc Three Terminal Negative Voltage Regulator**7905****• ELECTRICAL CHARACTERISTICS** $T_j=25^{\circ}\text{C}$ ($V_i=-10\text{V}$, $I_o=0.5\text{A}$, $C_i=2.2\ \mu\text{F}$, $C_o=1\ \mu\text{F}$ unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
V_o	Output Voltage	$V_{in}=-10\text{V}$; $I_o=500\text{mA}$	-4.8	-5.2	V
V_o	Output Voltage	$I_o=5\text{mA}$ to 1A ; $V_{in}=-7\text{V}$ to -20V	-4.75	-5.25	V
ΔV_v	Line Regulation	$-7\text{V} \leq V_{in} \leq -25\text{V}$		100	mV
ΔV_i	Load Regulation	$5\text{mA} \leq I_o \leq 1.5\text{A}$		100	mV
I_q	Quiescent Current	$V_{in}=10\text{V}$; $I_o=1.5\text{A}$		6	mA
Δq_1	Quiescent Current Change	$5\text{mA} \leq I_o \leq 1\text{A}$; $V_{in}=10\text{V}$		0.5	mA
Δq_2	Quiescent Current Change	$-8\text{V} \leq V_{in} \leq -25\text{V}$		0.8	mA