


80 Series

**Commercial Grade Acrasil[®], Silicone-Ceramic
Conformal Axial Terminal Wirewound
1% Tol. (5% avail.)**

RW Series

Military Grade 80 Series MIL-R-26 Qualified



| Comm. Grade | Military Grade | Watts | Ohms | Dimensions (in. / mm) | | Lead ga. |
|-------------|----------------|-------|----------|-----------------------|--------------|----------|
| | | | | Length | Diam. | |
| 81F | RW70U | 1 | 0.1-6K | 0.437 / 11.1 | 0.125 / 3.2 | 150 24 |
| 82 | | 2 | 0.1-8K | 0.406 / 10.3 | 0.219 / 5.6 | 100 20 |
| 83F | RW79U | 3 | 0.1-20K | 0.593 / 15.1 | 0.218 / 5.5 | 200 20 |
| 83J | RW69V | | | | | |
| 85F | RW74U | 5 | 0.1-75K | 0.937 / 23.8 | 0.343 / 8.7 | 460 18 |
| 85J | RW67V | | | | | |
| 80F | RW78U | 10 | 0.1-150K | 1.842 / 46.8 | 0.406 / 10.3 | 1000 18 |
| 80J | RW68V | | | | | |

Non-Inductive versions available. Insert "N" before tolerance code. Example: 83NF2K21

Ohmite's highest quality conformal axial terminal silicone-ceramic coated resistors for applications requiring high precision and stability. These resistors have a low temperature coefficient and maintain a high degree of stability under demanding conditions.

FEATURES

- Designed for precision power applications
- All-welded construction
- RW Series "Mil" value resistors marked with "Mil" in accordance with MIL-R-26 specifications

SPECIFICATIONS

Material

Coating: Silicone-ceramic.

Core: Ceramic.

Terminals: Solder-coated copper clad axial.

Derating: Linearly from 100% @ +25°C to 0% @ +275°C.

Electrical

Tolerance: ±5% (J type), ±1% (F type) (other tolerances available).

Power rating: Based on 25°C free air rating.

Maximum ohmic values: See chart.

Overload: Under 5 watts: 5 times rated wattage for 5 seconds. 5 watts and over: 10 times rated wattage for 5 seconds.

Temperature coefficient:

Under 1Ω: ±90 ppm/°C
1 to 9.99Ω: ±50 ppm/°C
10Ω and over: ±20 ppm/°C

Dielectric withstanding voltage:

500 VAC: 1 watt rating
1000 VAC: 2, 3, 5, 7 and 10 watt rating

ORDERING INFORMATION

Commercial Grade | Non-Inductive Winding
Optional (blank = std. winding)

81NJR10

| 80 Series | Wattage | Tolerance | Resistance Value |
|----------------------|---------|-----------|------------------|
| Acrasil [®] | 1 = 1W | F = 1% | R10 = 0.10Ω |
| Silicone Ceramic | 2 | J = 5% | 1R0 = 1.0Ω |
| Conformal Axial | 3 | | 10R = 10.0Ω |
| Term. Wirewound | 5 | | 250 = 250Ω |
| | 0 = 10W | | 1K0 = 1,000Ω |
| | | | 4K5 = 4,500Ω |
| | | | 50K = 50,000Ω |

Military Grade

RW74U1001F

| RW Series | Resistance Value | Tolerance |
|----------------|------------------|--------------|
| Military grade | R100 = 0.1Ω | F = 1% |
| | 1R00 = 1.0Ω | J = 5% |
| | 10R0 = 10.0Ω | |
| | 1000 = 1000Ω | 1002 = 10KΩ |
| | 1001 = 1000Ω | 1503 = 150KΩ |

This product will not be made available as RoHS Compliant.

For RoHS Compliant equivalent, see 40 Series.

COMMERCIAL GRADE PART NUMBERS

| Ohmic value | | Part No. Prefix Suffix | | Wattage | | | | Ohmic value | | Part No. Prefix Suffix | | Wattage | | | | Ohmic value | | Part No. Prefix Suffix | | Wattage | | | |
|-------------|------|------------------------|---|---------|---|---|----|-------------|------|------------------------|---|---------|---|---|----|-------------|------|------------------------|---|---------|----|--|--|
| | | | | 1 | 3 | 5 | 10 | | | | | 1 | 3 | 5 | 10 | | | | | 5 | 10 | | |
| 0.1 | R10 | ✓ | ✓ | ✓ | ✓ | | | 2.21 | 2R21 | ✓ | ✓ | ✓ | ✓ | | | 51.1 | 51R1 | ✓ | ✓ | ✓ | ✓ | | |
| 0.11 | R11 | ✓ | ✓ | ✓ | ✓ | | | 2.49 | 2R49 | ✓ | ✓ | ✓ | ✓ | | | 56.2 | 56R2 | ✓ | ✓ | ✓ | ✓ | | |
| 0.121 | R121 | ✓ | ✓ | ✓ | ✓ | | | 2.74 | 2R74 | ✓ | ✓ | ✓ | ✓ | | | 61.9 | 61R9 | ✓ | ✓ | ✓ | ✓ | | |
| 0.133 | R133 | ✓ | ✓ | ✓ | ✓ | | | 3.01 | 3R01 | ✓ | ✓ | ✓ | ✓ | | | 68.1 | 68R1 | ✓ | ✓ | ✓ | ✓ | | |
| 0.15 | R15 | ✓ | ✓ | ✓ | ✓ | | | 3.32 | 3R32 | ✓ | ✓ | ✓ | ✓ | | | 75 | 75R | ✓ | ✓ | ✓ | ✓ | | |
| 0.162 | R162 | ✓ | ✓ | ✓ | ✓ | | | 3.74 | 3R74 | ✓ | ✓ | ✓ | ✓ | | | 82.5 | 82R5 | ✓ | ✓ | ✓ | ✓ | | |
| 0.182 | R182 | ✓ | ✓ | ✓ | ✓ | | | 4.02 | 4R02 | ✓ | ✓ | ✓ | ✓ | | | 90.9 | 90R9 | ✓ | ✓ | ✓ | ✓ | | |
| 0.2 | R20 | ✓ | ✓ | ✓ | ✓ | | | 4.53 | 4R53 | ✓ | ✓ | ✓ | ✓ | | | 100 | 100 | ✓ | ✓ | ✓ | ✓ | | |
| 0.221 | R221 | ✓ | ✓ | ✓ | ✓ | | | 4.99 | 4R99 | ✓ | ✓ | ✓ | ✓ | | | 110 | 110 | ✓ | ✓ | ✓ | ✓ | | |
| 0.249 | R249 | ✓ | ✓ | ✓ | ✓ | | | 5.11 | 5R11 | ✓ | ✓ | ✓ | ✓ | | | 121 | 121 | ✓ | ✓ | ✓ | ✓ | | |
| 0.274 | R274 | ✓ | ✓ | ✓ | ✓ | | | 5.62 | 5R62 | ✓ | ✓ | ✓ | ✓ | | | 133 | 133 | ✓ | ✓ | ✓ | ✓ | | |
| 0.301 | R301 | ✓ | ✓ | ✓ | ✓ | | | 6.19 | 6R19 | ✓ | ✓ | ✓ | ✓ | | | 150 | 150 | ✓ | ✓ | ✓ | ✓ | | |
| 0.332 | R332 | ✓ | ✓ | ✓ | ✓ | | | 6.81 | 6R81 | ✓ | ✓ | ✓ | ✓ | | | 162 | 162 | ✓ | ✓ | ✓ | ✓ | | |
| 0.374 | R374 | ✓ | ✓ | ✓ | ✓ | | | 7.5 | 7R5 | ✓ | ✓ | ✓ | ✓ | | | 182 | 182 | ✓ | ✓ | ✓ | ✓ | | |
| 0.392 | R392 | ✓ | ✓ | ✓ | ✓ | | | 8.25 | 8R25 | ✓ | ✓ | ✓ | ✓ | | | 200 | 200 | ✓ | ✓ | ✓ | ✓ | | |
| 0.402 | R402 | ✓ | ✓ | ✓ | ✓ | | | 9.09 | 9R09 | ✓ | ✓ | ✓ | ✓ | | | 221 | 221 | ✓ | ✓ | ✓ | ✓ | | |
| 0.453 | R453 | ✓ | ✓ | ✓ | ✓ | | | 10 | 10R | ✓ | ✓ | ✓ | ✓ | | | 249 | 249 | ✓ | ✓ | ✓ | ✓ | | |
| 0.499 | R499 | ✓ | ✓ | ✓ | ✓ | | | 11 | 11R | ✓ | ✓ | ✓ | ✓ | | | 274 | 274 | ✓ | ✓ | ✓ | ✓ | | |
| 0.511 | R511 | ✓ | ✓ | ✓ | ✓ | | | 12.1 | 12R1 | ✓ | ✓ | ✓ | ✓ | | | 301 | 301 | ✓ | ✓ | ✓ | ✓ | | |
| 0.562 | R562 | ✓ | ✓ | ✓ | ✓ | | | 13.3 | 13R3 | ✓ | ✓ | ✓ | ✓ | | | 332 | 332 | ✓ | ✓ | ✓ | ✓ | | |
| 0.619 | R619 | ✓ | ✓ | ✓ | ✓ | | | 15 | 15R | ✓ | ✓ | ✓ | ✓ | | | 374 | 374 | ✓ | ✓ | ✓ | ✓ | | |
| 0.681 | R681 | ✓ | ✓ | ✓ | ✓ | | | 16.2 | 16R2 | ✓ | ✓ | ✓ | ✓ | | | 402 | 402 | ✓ | ✓ | ✓ | ✓ | | |
| 0.75 | R75 | ✓ | ✓ | ✓ | ✓ | | | 18.2 | 18R2 | ✓ | ✓ | ✓ | ✓ | | | 453 | 453 | ✓ | ✓ | ✓ | ✓ | | |
| 0.825 | R825 | ✓ | ✓ | ✓ | ✓ | | | 20 | 20R | ✓ | ✓ | ✓ | ✓ | | | 499 | 499 | ✓ | ✓ | ✓ | ✓ | | |
| 0.909 | R909 | ✓ | ✓ | ✓ | ✓ | | | 22.1 | 22R1 | ✓ | ✓ | ✓ | ✓ | | | 511 | 511 | ✓ | ✓ | ✓ | ✓ | | |
| 1 | R10 | ✓ | ✓ | ✓ | ✓ | | | 24.9 | 24R9 | ✓ | ✓ | ✓ | ✓ | | | 562 | 562 | ✓ | ✓ | ✓ | ✓ | | |
| 1.1 | R11 | ✓ | ✓ | ✓ | ✓ | | | 27.4 | 27R4 | ✓ | ✓ | ✓ | ✓ | | | 619 | 619 | ✓ | ✓ | ✓ | ✓ | | |
| 1.21 | R121 | ✓ | ✓ | ✓ | ✓ | | | 30.1 | 30R1 | ✓ | ✓ | ✓ | ✓ | | | 681 | 681 | ✓ | ✓ | ✓ | ✓ | | |
| 1.330 | R133 | ✓ | ✓ | ✓ | ✓ | | | 33.2 | 33R2 | ✓ | ✓ | ✓ | ✓ | | | 750 | 750 | ✓ | ✓ | ✓ | ✓ | | |
| 1.5 | R15 | ✓ | ✓ | ✓ | ✓ | | | 37.4 | 37R4 | ✓ | ✓ | ✓ | ✓ | | | 825 | 825 | ✓ | ✓ | ✓ | ✓ | | |
| 1.62 | R162 | ✓ | ✓ | ✓ | ✓ | | | 40.2 | 40R2 | ✓ | ✓ | ✓ | ✓ | | | 909 | 909 | ✓ | ✓ | ✓ | ✓ | | |
| 1.82 | R182 | ✓ | ✓ | ✓ | ✓ | | | 45.3 | 45R3 | ✓ | ✓ | ✓ | ✓ | | | 1,000 | 1K0 | ✓ | ✓ | ✓ | ✓ | | |
| 2 | R20 | ✓ | ✓ | ✓ | ✓ | | | 49.9 | 49R9 | ✓ | ✓ | ✓ | ✓ | | | 1,100 | 1K1 | ✓ | ✓ | ✓ | ✓ | | |

✓ = Standard values
✦ = Non-standard values subject to minimum handling charge per item

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.

Check product availability at www.ohmite.com