



DESCRIPTION

The A7805A is available in TO-252 package.


FEATURES

- Maximum output current I_{OM} : 1.5A
- Output voltage V_o : 5V
- Continuous total dissipation P_D :
1.25W ($T_A = 25^\circ\text{C}$)
10 W($T_C = 25^\circ\text{C}$)
- Available in TO-252 package

ORDERING INFORMATION


Package Type	Part Number	
TO-252 SPQ: 2,500pcs/Reel	D	A7805ADR
		A7805ADVR
Note	V: Halogen free Package R: Tape & Reel	
AiT provides all RoHS products		

TYPICAL APPLICATION





PIN DESCRIPTION



Top View

Pin #	Symbol	Function
1	IN	Input
2	GND	Ground
3	OUT	Output



ABSOLUTE MAXIMUM RATINGS

Operating temperature range applies, unless otherwise specified

V _{IN} , Input Voltage	35V
R _{θJA} , Thermal Resistance from Junction to Air	100°C/W
R _{θJC} , Thermal Resistance from Junction to Case	12.5°C/W
T _{OPR} , Operating Junction Temperature Range	0°C ~ 125°C
T _{STG} , Storage Temperature Range	-65°C~+150°C

Stress beyond above listed "Absolute Maximum Ratings" may lead permanent damage to the device. These are stress ratings only and operations of the device at these or any other conditions beyond those indicated in the operational sections of the specifications are not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS


V_I=10V, I_o=500mA, C_i=0.33μF, C_o=0.1μF, unless otherwise specified

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Output Voltage	V _o	25°C	4.8	5.0	5.2	V
		7V≤V _I ≤20V, I _o =5mA-1A, P≤10W 0-125°C	4.75	5.00	5.25	
Load Regulation	ΔV _o	I _o =5mA-1.5A 25°C	-	9	100	mV
		I _o =250mA-750mA 25°C	-	4	50	
Line Regulation	ΔV _o	7V≤V _I ≤25V 25°C	-	4	100	mV
		8V≤V _I ≤12V 25°C	-	1.6	50	
Quiescent Current	I _q	25°C	-	5.0	8.0	mA
Quiescent Current Change	ΔI _q	7V≤V _I ≤25V 0-125°C	-	0.3	1.3	mA
		5mA≤I _o ≤1A 0-125°C	-	0.03	0.5	
Output Noise Voltage	V _N	10Hz≤f≤100KHz 25°C	-	42	-	μV
Output Voltage Drift	ΔV _o /ΔT	I _o =5.0mA 0-125°C	-	-1.1	-	mV/°C
Ripple Rejection	RR	f=120Hz, V _I =8V to 18V 0-125°C	62	73	-	dB
Dropout Voltage	V _d	I _o =1A 25°C	-	2	-	V
Output resistance	R _o	f=1KHz 25°C	-	10	-	mΩ
Short Circuit Current	I _{sc}	25°C	-	230	-	mA
Peak Current	I _{PK}	25°C	-	2.2	-	A




TYPICAL PERFORMANCE CHARACTERISTICS


1. Output Characteristics




2. Dropout Characteristics




3. Quiescent Current vs. Input Voltage




4. Quiescent Current vs. Output Current



5. Output Voltage vs. Ambient Temperature




6. Current Cut-off Grid Voltage






7. Power De rating Curve





PACKAGE INFORMATION

Dimension in TO-252-3 (Unit: mm)



Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A	2.200	2.380	0.087	0.094
A1	0.000	0.100	0.000	0.004
B	0.800	1.400	0.031	0.055
b	0.710	0.810	0.028	0.032
c	0.460	0.560	0.018	0.022
c1	0.460	0.560	0.018	0.022
D	6.500	6.700	0.256	0.264
D1	5.130	5.460	0.202	0.215
E	6.000	6.200	0.236	0.244
e	2.286 TYP.		0.090 TYP	
e1	4.327	4.727	0.170	0.186
M	1.778REF.		0.070REF.	
N	0.762REF.		0.018REF.	
L	9.800	10.400	0.386	0.409
L1	2.9REF.		0.114REF.	
L2	1.400	1.700	0.055	0.067
V	4.830 REF.		0.190 REF.	
Φ	1.100	1.300	0.043	0.051



IMPORTANT NOTICE

AiT Semiconductor Inc. (AiT) reserves the right to make changes to any its product, specifications, to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

AiT Semiconductor Inc.'s integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life support applications, devices or systems or other critical applications. Use of AiT products in such applications is understood to be fully at the risk of the customer. As used herein may involve potential risks of death, personal injury, or severe property, or environmental damage. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

AiT Semiconductor Inc. assumes to no liability to customer product design or application support. AiT warrants the performance of its products of the specifications applicable at the time of sale.