

## Data Sheet




### Description

The ACPL-827 is a DC-input dual channel full-pitch phototransistor optocoupler which contains two light emitting diode optically coupled to two separate transistor. It is packaged in a 8-pin DIP package.

Likewise, the ACPL-847 is a DC-input quad channel full-pitch phototransistor optocoupler which contains four light emitting diode optically coupled to four separate transistor. It is packaged in a 16-pin DIP package


For both types, it is also available in wide-lead spacing option and lead bend SMD option with input-output isolation voltage at 5000 Vrms. Response time,  $t_r$ , is typically 4  $\mu$ s and minimum CTR is 50% at input current of 5 mA

#### ACPL-827 pin layout



- Pin 1, 3 Anode
- Pin 2, 4 Cathode
- Pin 5, 7 Emitter
- Pin 6, 8 Collector

#### ACPL-847 pin layout



- Pin 1, 3, 5, 7 Anode
- Pin 2, 4, 6, 8 Cathode
- Pin 9, 11, 13, 15 Emitter
- Pin 10, 12, 14, 16 Collector

### Features

- Current transfer ratio (CTR: min. 50% at  $I_F = 5\text{mA}$ ,  $V_{CE} = 5\text{V}$ )
- High input-output isolation voltage ( $V_{ISO} = 5,000V_{RMS}$ )
- Response time ( $t_r$ : typ. 4 $\mu$ s at  $V_{CE} = 2\text{V}$ ,  $I_C = 2\text{mA}$ ,  $R_L = 100\Omega$ )
- Compact dual-in-line package
- Safety and regulatory approvals
  - CSA
  - UL 1577
  - IEC/EN/DIN EN 60747-5-2
- Options available:
  - Leads with 0.4" (10.16 mm) spacing (W00)
  - Lead bend for surface mounting (300)
  - Tape and reel for SMD (500) – available only for ACPL-827
  - IEC/EN/DIN EN 60747-5-2 approved (060)
  - Lead-Free (000E)

### Applications

- I/O Interface for Programmable controllers, computers.
- Sequence controllers
- System appliances, measuring instruments
- Signal transmission between circuits of different potentials and impedances.

## Ordering Information

ACPL-8x7 is UL Recognized with 5000 Vrms for 1 minute per UL1577 and is approved under CSA Component Acceptance Notice #5, File CA 88324.

Part number	RoHS Compliant Option				Package	No. of Channels	Surface Mount	Gull Wing	Tape & Reel	IEC/EN/DIN EN 60747-5-2	Quantity	
	Rank 'O' 50% <CTR< 600%	Rank 'B' 130% <CTR< 260%	Rank 'C' 200% <CTR< 400%	Rank 'G' 130% <CTR< 400%								
ACPL-827	-000E	-00BE	-00CE		300mil DIP-8						50 pcs per tube	
	-300E	-30BE	-30CE		300mil DIP-8		x	X			50 pcs per tube	
	-500E	-50BE	-50CE		300mil DIP-8		X	X	X		1000 pcs per reel	
	-060E	-06BE	-06CE		300mil DIP-8	Dual				X	50 pcs per tube	
	-360E	-36BE	-36CE		300mil DIP-8		x	X		X	50 pcs per tube	
	-560E	-56BE	-56CE		300mil DIP-8		x	X	X	X	1000 pcs per reel	
	-W00E	-W0BE	-W0CE		400mil DIP-8							50 pcs per tube
	-W60E	-W6BE	-W6CE		400mil DIP-8						X	50 pcs per tube
-000E			-00GE	300mil DIP-16							25 pcs per tube	
-300E			-30GE	300mil DIP-16			X	X			25 pcs per tube	
-060E			-06GE	300mil DIP-16	Quad					X	25 pcs per tube	
-360E			-36GE	300mil DIP-16		X	X		X	25 pcs per tube		
-W00E			-W0GE	400mil DIP-16							25 pcs per tube	
-W60E			-W6GE	400mil DIP-16						X	25 pcs per tube	

To order, choose a part number from the part number column and combine with the desired option from the option column to form an order entry.

Example 1:

ACPL-827-36GE to order product of 300mil DIP-8 Dual Channel DC Gull Wing Surface Mount package in Tube packaging with 130%<CTR<400%, IEC/EN/DIN EN 60747-5-2 Safety Approval and RoHS compliant.


Example 2:

ACPL-847-W00E to order product of 400mil DIP-16 Quad Channel DC package in Tube packaging with 50%<CTR<600% and RoHS compliant.

Option datasheets are available. Contact your Avago sales representative or authorized distributor for information.


# Package Outline Drawings

## ACPL-827 Package Outline




DIMENSIONS IN [MILLIMETERS] AND INCHES




## ACPL-827 Package Outline – Option 060



DIMENSIONS IN [MILLIMETERS] AND INCHES






**ACPL-827 Package Outline – Option W00**




DIMENSIONS IN [MILLIMETERS] AND INCHES

**ACPL-827 Package Outline – Option 300**




DIMENSIONS IN [MILLIMETERS] AND INCHES

### ACPL-847 Package Outline






DIMENSIONS IN [MILLIMETERS] AND INCHES

### ACPL-847 Package Outline - Option 060






DIMENSIONS IN [MILLIMETERS] AND INCHES

### ACPL-847 Package Outline - Option W00



DIMENSIONS IN [MILLIMETERS] AND INCHES

### ACPL-847 Package Outline - Option 300




DIMENSIONS IN [MILLIMETERS] AND INCHES

### Solder Reflow Temperature Profile

1. One-time soldering reflow is recommended within the condition of temperature and time profile shown at right.
2. When using another soldering method such as infrared ray lamp, the temperature may rise partially in the mold of the device. Keep the temperature on the package of the device within the condition of (1) above.

Note: Non-halide flux should be used.



## Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Units	Note
Storage Temperature	$T_S$	-55	125	°C	
Operating Temperature	$T_A$	-30	100	°C	
Average Forward Current	$I_{F(AVG)}$	-	50	mA	
Input Power Dissipation	$P_I$	-	70	mW	
Input Reverse Voltage	$V_R$	-	6	V	
Collector Current	$I_C$	-	50	mA	
Collector-Emitter Voltage	$V_{CEO}$	-	70	V	
Emitter-Collector Voltage	$V_{ECO}$	-	6	V	
Isolation Voltage (AC for 1min, R.H. 40~60%)	$V_{ISO}$	-	5000	$V_{RMS}$	
Collector Power Dissipation	$P_C$	-	150	mW	
Total Power Dissipation	$P_{TOT}$	-	200	mW	
Lead Solder Temperature		260°C for 10 sec., 1.6 mm below seating plane			

## Electrical Specifications (DC)

Over recommended operating conditions unless otherwise specified.

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions	Note
Forward Voltage	$V_F$	-	1.2	1.4	V	$I_F = 20\text{mA}$	
Reverse Current	$I_R$	-	-	10	$\mu\text{A}$	$V_R = 4\text{V}$	
Terminal Capacitance	$C_t$		30	250	pF	$V = 0, f = 1\text{KHz}$	
Collector Dark Current	$I_{CEO}$		-	100	nA	$V_{CE} = 20\text{V}, I_F = 0\text{mA}$	
Collector-Emitter Breakdown Voltage	$BV_{CEO}$	70	-	-	V	$I_C = 0.1\text{mA}, I_F = 0\text{mA}$	
Emitter-Collector Breakdown Voltage	$BV_{ECO}$	6	-	-	V	$I_E = 10\mu\text{A}, I_F = 0\text{mA}$	
Collector Current	$I_C$	2.5	-	30	mA	$I_F = 5\text{mA}, V_{CE} = 5\text{V}$	$CTR = (I_C/I_F) * 100\%$
Current Transfer Ratio	CTR	50	-	600	%		
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	-	0.1	0.2	V	$I_F = 20\text{mA}, I_C = 1\text{mA}$	
Isolation Resistance	$R_{ISO}$	$5 \times 10^{10}$	$1 \times 10^{11}$	-	$\Omega$	DC500V, R.H. 40~60%	
Floating Capacitance	$C_F$	-	0.6	1	pF	$V = 0, f = 1\text{MHz}$	
Cut-off Frequency (-3dB)	$F_C$	-	80	-	KHz	$V_{CE} = 5\text{V}, I_C = 2\text{mA}, RL = 100\Omega$	See fig 13
Response Time (Rise)	$t_r$	-	4	18	$\mu\text{s}$	$V_{CE} = 2\text{V}, I_C = 2\text{mA}, RL = 100\Omega$	See fig 12
Response Time (Fall)	$t_f$	-	3	18	$\mu\text{s}$		




Figure 1. Forward Current vs. Ambient Temperature.




Figure 2 Collector Power Dissipation vs. Ambient Temperature




Figure 3. Collector-emitter Saturation Voltage vs. Forward Current




Figure 4. Forward Current vs. Forward Voltage




Figure 5. Current Transfer Ratio vs. Forward Current




Figure 6. Collector Current vs. Collector-emitter Voltage.






Figure 7. Relative Current Transfer Ratio vs. Ambient Temperature




Figure 8. Collector-emitter Saturation Voltage vs. Ambient Temperature




Figure 9. Collector Dark Current vs. Ambient Temperature




Figure 10. Response Time vs. Load Resistance




Figure 11. Frequency Response




Figure 12. Test Circuit for Response Time




Figure 13. Test Circuit for Frequency Response

For product information and a complete list of distributors, please go to our web site: [www.avagotech.com](http://www.avagotech.com)

Avago, Avago Technologies, and the A logo are trademarks of Avago Technologies in the United States and other countries. Data subject to change. Copyright © 2005-2008 Avago Technologies. All rights reserved. Obsoletes AV01-0612EN AV02-1429EN - December 22, 2008

**Avago**  
TECHNOLOGIES