

isc N-Channel MOSFET Transistor
STF9NK90Z
FEATURES

- Drain Current : $I_D = 8A @ T_C = 25^\circ C$
- Drain Source Voltage
: $V_{DSS} = 900V(\text{Min})$
- Static Drain-Source On-Resistance
: $R_{DS(on)} = 1.3 \Omega (\text{Max}) @ V_{GS} = 10V$
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

DESCRIPTION



- motor drive, DC-DC converter, power switch and solenoid drive.

• ABSOLUTE MAXIMUM RATINGS($T_a = 25^\circ C$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{DSS}	Drain-Source Voltage	900	V
V_{GSS}	Gate-Source Voltage	± 30	V
I_D	Drain Current-Continuous; @ $T_C = 25^\circ C$	8	A
I_{DM}	Drain Current-Single Pulsed	32	A
P_D	Total Dissipation	40	W
T_j	Operating Junction Temperature	-55~150	$^\circ C$
T_{stg}	Storage Temperature	-55~150	$^\circ C$

• THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th(ch-c)}$	Channel-to-case thermal resistance	3.1	$^\circ C/W$



isc N-Channel MOSFET Transistor

STF9NK90Z

ELECTRICAL CHARACTERISTICS

T_c=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V; I _D = 1mA	900	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} ; I _D = 0.1mA	3	-	4.5	V
R _{DS(on)}	Drain-Source On-Resistance	V _{GS} =10V; I _D =3.6A	-	-	1.3	Ω
I _{GSS}	Gate-Source Leakage Current	V _{GS} =±20V; V _{DS} = 0V	-	-	±10	uA
I _{DSS}	Drain-Source Leakage Current	V _{DS} = 900V; V _{GS} = 0V	-	-	1	uA
V _{SD}	Diode forward voltage	I _{SD} = 8A, V _{GS} = 0 V	-	-	1.6	V

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.