



NXP 50-MHz, 32-bit ARM Cortex-M0™ microcontrollers LPC11U00

Low-cost Cortex-M0 USB solutions with Smart Card interface

Delivering robust USB performance at a low price point, these low-cost devices are compelling replacements for 8/16-bit USB microcontrollers. The highly flexible USB architecture is, quite simply, a better approach to USB. NXP offers the widest range of ARM-based USB solutions, as well as easy-to-use software and integrated development platforms that make NXP a one-stop shop for USB.

Features

- ▶ ARM Cortex-M0 processor, running at frequencies of up to 50 MHz
- ▶ Memory:
 - Up to 32 kB on-chip flash program memory
 - Total of 6 kB SRAM data memory (4 kB main SRAM and 2 kB USB SRAM)
 - 16 kB boot ROM
 - In-System Programming (ISP) and In-Application Programming (IAP) via on-chip bootloader software
- ▶ Debug options:
 - Standard JTAG test/debug interface. Serial Wire Debug
 - Boundary scan for simplified board testing
- ▶ Up to 40 General-Purpose I/O (GPIO) pins with configurable pull-up/pull-down resistors, repeater mode, and open-drain mode
 - Two GPIO grouped interrupt modules enable an interrupt based on a programmable pattern of input states of a group of GPIO pins
 - High-current source output driver (20 mA) on one pin (P0_7)
 - High-current sink driver (20 mA) on two true open-drain pins (P0_4 and P0_5)
- ▶ Four general-purpose counter/timers with a total of up to 5 capture inputs and 13 match outputs
- ▶ Programmable Windowed WatchDog Timer (WWDT) with a dedicated, internal low-power WatchDog Oscillator (WDO)
- ▶ Analog peripherals:
 - 10-bit ADC with input multiplexing among eight pins
- ▶ Serial interfaces:
 - USB 2.0 full-speed device controller
 - USART with fractional baud-rate generation
 - USART supports an asynchronous Smart Card interface (ISO 7816-3)
 - Two SSP controllers with FIFO and multi-protocol capabilities
 - I²C-bus interface supporting the full I²C-bus specification and Fast-mode Plus (Fm+)



- ▶ Clock generation:
 - Crystal oscillator with an operating range of 1 to 25 MHz (system oscillator)
 - 12 MHz high-frequency Internal RC oscillator (IRC)
 - Internal low-power, low-frequency WatchDog Oscillator
 - PLL allows CPU operation up to the maximum CPU rate with the system oscillator or the IRC as clock sources
 - A second, dedicated PLL is provided for USB
 - Clock output function
- ▶ Power control:
 - Four reduced power modes: Sleep, Deep-sleep, Power-down, and Deep power-down
 - Power profiles residing in boot ROM
 - Processor wake-up from Deep-sleep and Power-down modes via reset, selectable GPIO pins, watchdog interrupt, or USB port activity
- ▶ Power-On Reset (POR)
- ▶ Brownout detect with four separate thresholds for interrupt and forced reset

- ▶ Unique device serial number for identification
- ▶ Single 3.3 V power supply (1.8 to 3.6 V)
- ▶ Temperature range -40 to +85°C
- ▶ Available in 48-pin LQFP, 48-pin TFBGA, and 33-pin HVQFN package
- ▶ Pin-compatible with the LPC134x series


Maximizing connectivity, minimizing power

Connectivity options on the LPC11U00 series include two Synchronous Serial Port (SSP) interfaces, I²C with Fast-mode Plus feature for 10x higher bus-drive capability, a Universal Synchronous-Asynchronous Receiver/Transmitter (USART) and a Smart Card interface. The Smart Card interface (ISO7816-3) provides a plug-and-play interface for Smart Cards, making the LPC11U00 a good fit for e-commerce applications.

Small form-factor mobile & consumer apps

As an extension of NXP's proven LPC1100 family, the LPC11U00 series delivers up to 32 kB Flash, 6 kB SRAM, a variety of serial interfaces, four system timers with PWM functionality, an 8-channel, 10-bit ADC, and up to 40 GPIOs. In addition to several standard package offerings, the LPC11U00 series is offered in a miniature 4.5 x 4.5 mm TFBGA48 package, making it especially suited for small form-factor mobile and consumer applications.

LPC11U1x



Type number	Flash	Total SRAM	USB	USART/Smart Card Interface	I ² C / Fm+	ADC channels	SSP	Package
LPC11U12FHN33/201	16 kB	6 kB	1	1	1	8	2	HVQFN33
LPC11U12FBD48/201	16 kB	6 kB	1	1	1	8	2	LQFP48
LPC11U13FBD48/201	24 kB	6 kB	1	1	1	8	2	LQFP48
LPC11U14FHN33/201	32 kB	6 kB	1	1	1	8	2	HVQFN33
LPC11U14FBD48/201	32 kB	6 kB	1	1	1	8	2	LQFP48
LPC11U14FET48/201	32 kB	6 kB	1	1	1	8	2	TFBGA48

www.nxp.com

© 2011 NXP Semiconductors N.V.

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Date of release: April 2011

Document order number: 9397 750 17080

Printed in the Netherlands