

PH150A280-24



<b>Sales Region</b>	Worldwide
<b>Series</b>	PH-A280
<b>Status</b>	Production
<b>Option</b>	
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



### Electrical Characteristics

Rated Input Voltage[DC]	280V
Input Voltage Range[DC]	200 to 425V
Efficiency	89% Typ.
Rated Output Voltage[DC]	24V
Output Voltage Range[DC]	19.2 to 26.4V
Maximum Output Current	
Maximum Ripple Noise	240mV
Maximum Output Power	151.2W
Withstanding Voltage1	Input - Base plate: 2500VAC: 1min.
Withstanding Voltage2	Input - Output: 3000VAC: 1min.
Withstanding Voltage3	Output - Base plate: 500VAC: 1min.

### Cases Shape & Size

Case'□ shape	On board/Power module
Width(W)	37.2mm Nom.
Height(H)	12.7mm Nom.
Depth(D)	58.3mm Nom.
Weight	55g Typ.
Industry Standard Size	1/4 brick size
Terminal Style	DIP

### Other

Operating Temp. Range	-40 to 85°C
Isolated / Non-isolated	Isolated
Feature	With baseplate
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 EN60950-1
Safety Standard(Conformed)	

