


VS75E-12/CO2



Sales Region	Worldwide
Series	VS-E
Status	 Production
Feature	
Option	With coating on both sides of PCB model
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage Range[AC]	85 to 132V
Input Voltage Range[DC]	
Efficiency	85% Typ.
Rated Output Voltage[DC]	12V
Output Voltage Range[DC]	10.8 to 13.2V
Maximum Output Current	6.3A
Maximum Output Power	75.6W

Cases Shape & Size

Case'□ shape	PC board
Width(W)	50mm Nom.
Height(H)	29mm Nom.
Depth(D)	150mm Nom.
Weight	200g Typ.

Other

Operating Temp. Range	-10 to 70°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
Safety Standard(Conformed)	EN50178 (OV II)
	Den-an Appendix 12
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.